



#### NOTES:

- Each edge of the Proglaze ETA Connections set in 1" minimum bead of Spectrem 1 silicone sealant - refer to application instructions for more detail on installation
- Width of Proglaze ETA Connections determined by width of joint/gap and anticipated movement
- 3" Overlap sealed with Spectrem 1 for Proglaze ETA Connections splicing, applied in proper shingle effect
- Should not be used with adhesively attached cladding

See [securockexoair.com](http://securockexoair.com) for the most up-to-date product information

*This detail is intended for conceptual purposes only. Must be reviewed by a project/design professional*

*The following trademarks used herein are owned by USG Corporation or its subsidiaries: SECUROCK, USG, USG in stylized letters. The following trademarks used herein are owned by Tremco Incorporated or its subsidiaries: Tremco, ExoAir, Spectrem, Dymonic, Proglaze, Vulkem.*



**United States Gypsum Company**  
550 West Adams Street  
Chicago, IL 60661

USG Technical & Customer Support:  
800.USG.4YOU (874-4968)

**Tremco Commercial Sealants & Waterproofing**  
3735 Green Road  
Beachwood, OH 44122

Tremco Technical Support:  
866.209.2404

**SECUROCK® ExoAir® 430 Panel**

Project:

Detail: Expansion/Control Joint - Proglaze ETA Connections

Drawn by: KAB

Approved by: DM

Scale: NTS

File Name:

12888

Rev #

00

Date: 3/21/2017