



## NOTES:

- Minimum depth of bellow to be equal to the thickness of the Securock ExoAir 430 Panel
- Exact depth of bellow to be determined by anticipated movement
- Overlap 1" of ExoAir Duo using Dymonic 100 when splicing in a proper shingle effect

See [securockexoair.com](http://securockexoair.com) for the most up-to-date product information

*This detail is intended for conceptual purposes only. Must be reviewed by a project/design professional*

*The following trademarks used herein are owned by USG Corporation or its subsidiaries: SECUROCK, USG, USG in stylized letters. The following trademarks used herein are owned by Tremco Incorporated or its subsidiaries: Tremco, ExoAir, Spectrem, Dymonic, Proglaze, Vulkem.*

-	-	-	-
Rev	Date	Description	By



**PERFORMANCE BUILT IN**  
www.securockexoair.com

**United States Gypsum Company**  
550 West Adams Street  
Chicago, IL 60661

USG Technical & Customer Support:  
800.USG.4YOU (874-4968)

**Tremco Commercial Sealants & Waterproofing**  
3735 Green Road  
Beachwood, OH 44122

Tremco Technical Support:  
866.209.2404

**SECUROCK® ExoAir® 430 Panel**

Project: XXXX

Detail: Expansion Joint - ExoAir Duo

Drawn by: MI

Approved by: XX

Scale: NTS

File Name:

**12904**

Date: 7/9/2015

Rev #  
**00**