



**NOTES:**

- Slope to the exterior 1/8" per 12"
- Apply Dymonic 100 at 40 wet mils
- Flashing must be installed past thermal break

See [securockexoair.com](http://securockexoair.com) for the most up-to-date product information

*This detail is intended for conceptual purposes only. Must be reviewed by a project/design professional*

*The following trademarks used herein are owned by USG Corporation or its subsidiaries: SECUROCK, USG, USG in stylized letters. The following trademarks used herein are owned by Tremco Incorporated or its subsidiaries: Tremco, ExoAir, Spectrem, Dymonic, Proglaze, Vulkem.*



**PERFORMANCE BUILT IN**  
www.securockexoair.com

**United States Gypsum Company**  
550 West Adams Street  
Chicago, IL 60661

USG Technical & Customer Support:  
800.USG.4YOU (874-4968)

**Tremco Commercial Sealants & Waterproofing**  
3735 Green Road  
Beachwood, OH 44122

Tremco Technical Support:  
866.209.2404

**SECUROCK® ExoAir® 430 Panel**

Project:  
Detail: Rough Opening - Dymonic 100 - Wood Buck

Drawn by: KAB

Approved by: DM

Scale: NTS

File Name:

**14113**

Rev #

**00**

Date: 3/20/2017