



#### NOTES:

- Minimum 3" overlap required for all dissimilar materials and/or change in plane
- Install reinforcing mesh with 70 wet mils of ExoAir 230, completely covering reinforcing mesh

See [securockexoair.com](http://securockexoair.com) for the most up-to-date product information

*This detail is intended for conceptual purposes only. Must be reviewed by a project/design professional*

*The following trademarks used herein are owned by USG Corporation or its subsidiaries: SECUROCK, USG, USG in stylized letters. The following trademarks used herein are owned by Tremco Incorporated or its subsidiaries: Tremco, ExoAir, Spectrem, Dymonic, Proglaze, Vulkem.*



**PERFORMANCE BUILT IN**  
[www.securockexoair.com](http://www.securockexoair.com)

**United States Gypsum Company**  
550 West Adams Street  
Chicago, IL 60661

USG Technical & Customer Support:  
800.USG.4YOU (874-4968)

**Tremco Commercial Sealants & Waterproofing**  
3735 Green Road  
Beachwood, OH 44122

Tremco Technical Support:  
866.209.2404

**SECUROCK® ExoAir® 430 Panel**

Project:  
Detail: Wall to Below Grade

Drawn by: KAB

Approved by: DM

Scale: NTS

File Name:  
**12788**

Date: 3/29/2017

Rev #  
**00**