

4" DUROCK TAPE

ELASTOMERIC MEMBRANE. SEE NOTE BELOW

4" DUROCK TAPE AT JOINTS

1/2" RIGID INSULATION

WATER BARRIER

DUROCK EXTERIOR CEMENT BD.

WINDOW UNIT

BACKER ROD & SEALANT

WINDOW UNIT

ZINC FLASHING

BACKER ROD & SEALANT

BLOCKING AS REQ'D.

20 MIL ELASTOMERIC SHEET MEMBRANE NOBLESEAL 220 OR EQUAL.

4" DUROCK TAPE

PLYWOOD DECKING

NOTE: OVERLAP WATER BARRIER

SEALANT


DUROCK EXTERIOR CEMENT BOARD

NO. 093 CONTROL JOINT AS REQ'D.

1/2" RIGID INSULATION

WATER BARRIER

NOTE:
 1. DUROCK TAPE TO BE SET IN DUROCK EXTERIOR BASECOAT.
 2. DUROCK ECB TO BE BASECOATED WITH DUROCK EXTERIOR BASECOAT.
 3. SURFACE TO BE FINISHED WITH DUROCK EXTERIOR FINISH.



20 MIL ELASTOMERIC SHEET MEMBRANE. CUT & PATCH AT CORNER. SEAM WITH SOLVENT WELDING OR THERMAL WELDING.

WINDOW SILL DETAIL

SCALE: N.T.S.

DATE: 7/22/91

230