ForceField® Weather Barrier System
Inside Corner - Tape Method



GP Wood Products LLC
133 Peachtree St NE
Atlanta GA, 30303
Toll Free: 1-800-225-6119
www.forcefield.buildgp.com

Detail Notes:

1. Where tape splices occur overlap a minimum of 2".

2. Tapes must be installed using shingle lap application.

Manufacturer's Notes:

- Refer to the Installation Guide for the ForceField® Weather Barrier System, APA publications for installation requirements, and follow all applicable local building code requirements.
- Provide 1/8" spacing between panels and a minimum 1/2" gap when abutting masonry or concrete.
- Terminate system a minimum 6" distance above finished grade and a minimum 2" above hardscapes such as sidewalks and patios.

THIS DRAWING IS FOR GENERAL INFORMATION AND GUIDANCE AND INTENDED SOLELY FOR USE BY ARCHITECTS, ENGINEERS AND OTHER PROFESSIONALS FOR PLANNING PURPOSES. THIS DRAWING MAY NOT BE APPROPRIATE FOR ALL PROJECTS, ASSEMBLIES, SYSTEMS OR CONDITIONS. AND IN NO EVENT SHALL THIS DRAWING BE USED FOR CONSTRUCTION. ULTIMATELY, THE DESIGN AND DETAILING OF THE PROJECT, ASSEMBLY OR SYSTEM IS THE RESPONSIBILITY OF A PROFESSIONAL, AND ALL PROJECTS MUST COMPLY WITH APPLICABLE BUILDING CODES AND STANDARDS. GP WOOD PRODUCTS DISCLAIMS ANY RESPONSIBILITY OR LIABILITY FOR THE USE OF THIS DRAWING AND FOR THE ARCHITECTURE, DESIGN, ENGINEERING OR WORKMANSHIP OF ANY PROJECT, ASSEMBLY OR SYSTEM. ANY PRODUCTS MANUFACTURER BY PERSONS OTHER THAN GEORGIA-PACIFIC WOOD PRODUCTS ARE PRESENTED FOR ILLUSTRATION ONLY. PLEASE CONTACT THE MANUFACTURER OF SUCH PRODUCTS FOR INSTALLATION INSTRUCTIONS. GP WOOD PRODUCTS MAKES NO REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, CONCERNING THIS DRAWING AND SPECIFICALLY DISCLAIMS ANY IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR USE.

Issued Date	10/16/2020

FF-002

©2020 GP WOOD PRODUCTS LLC. ALL RIGHTS RESERVED. UNLESS OTHERWISE NOTED ALL TRADEMARKS ARE OWNED BY OR LICENSED TO GP WOOD PRODUCTS.